



DERWENT-ACC-NO: 1998-504308

DERWENT-WEEK: 199843

COPYRIGHT 2006 DERWENT INFORMATION LTD

TITLE: Wash basin fitted on front-loading washing machine

INVENTOR: NIKITIN YU, L

PATENT-ASSIGNEE: NIKITIN YU F[NIKII]

PRIORITY-DATA: 1996RU-0114012 (July 11, 1996)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
RU 2106105 C1	March 10, 1998	N/A	004	A47K 004/00

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO	APPL-DATE
RU 2106105C1	N/A	1996RU-0114012	July 11, 1996

INT-CL (IPC): A47K004/00, D06F029/00

ABSTRACTED-PUB-NO: RU 2106105C

BASIC-ABSTRACT:

The wash basin comprises a basin (1) with a throat (2) connected by a drainage pipe (3) to the drainage system, and is located on a washing machine connected by a hose (6) to the drainage and by taps to water supply.

The basin is fitted on a front loading washing machine (5) and is provided with a cut-off element (7). The basin drainage pipe is elastic. The washing machine drainage hose is provided with a covering element (8).

The basin drainage pipe has a slot cross-section which becomes narrow in the vertical direction. The basin mixer, its hot and cold taps and the hot and cold taps connected to the washing machine are connected by pipes into a block, which is located in a panel fitted on the wall.

The basin is cup-shaped, fitted in a rectangular cowl, located on top of the washing machine. The cup is rigidly connected to the cowl by a lid and bolts. The cup, cowl and the lid can be made as one whole by stamping.

The basin cut-off element and be manually reciprocated and can be located in the throat or the drainage pipe.

The drainage hose covering element is manually operated and can be made as a ball valve or a non-return valve.